

PENNZOIL PLATINUM VELOCITY SAE 0W-20

FULLY SYNTHETIC (API SQ)



PRODUCT DESCRIPTION

PENNZOIL PLATINUM VELOCITY SAE 0W-20 is a premium fully synthetic passenger car motor oil formulated to meet the latest API SQ and ILSAC GF-7A performance standards. Developed using advanced synthetic base oils and carefully selected additive technology, it is designed to deliver reliable lubrication, excellent oxidation stability and consistent lubricant performance throughout the recommended oil drain interval. Its balanced formulation also provides dependable low-temperature fluidity and viscosity stability to support effective engine protection across a wide range of operating conditions.

APPLICATION

PENNZOIL PLATINUM VELOCITY SAE 0W-20 is recommended for use in modern gasoline-powered passenger cars, SUVs and light commercial vehicles requiring an SAE 0W-20 engine oil meeting API SQ and ILSAC GF-7A performance requirements. It is suitable for naturally aspirated, turbocharged and gasoline direct injection (GDI/TGDI) engines operating under a wide range of driving conditions. For optimum engine protection and performance, always follow the oil change intervals and recommendations provided by the Original Equipment Manufacturer (OEM).

BENEFITS

- Advanced protection against Low Speed Pre-Ignition (LSPI) in modern turbocharged gasoline engines.
- Enhanced timing chain wear protection for improved engine durability.
- Helps minimize sludge and varnish deposits to maintain engine cleanliness.
- Excellent oxidation stability for consistent lubricant performance throughout the recommended oil drain interval.
- Outstanding low-temperature fluidity for rapid oil circulation during cold engine start-up.
- Optimized low-viscosity formulation to help improve fuel economy.

SPECIFICATIONS

- API SQ
- ILSAC GF-7A

PENNZOIL PLATINUM VELOCITY SAE 0W-20
FULLY SYNTHETIC (API SQ)



TYPICAL PROPERTIES

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 0W-20
API Service Category		API SQ
Density @30°C, kg/l	ASTM D4052	0.8376
Kinematic Viscosity @40°C, cSt @100°C, cSt	ASTM D445 ASTM D445	45.1 8.6
Viscosity Index	ASTM D2270	170
Flash Point, °C	ASTM D92	220
Pour Point, °C	ASTM D5950	-45
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 6200 @ -35
Total Base Number, mgKOH/g	ASTM D2896	8.0