

PENNZOIL FASTRAC TITANIUM 4T SEMI SYNTHETIC SAE 10W-40 (API SP)



PRODUCT DESCRIPTION

PENNZOIL FASTRAC TITANIUM 4T SEMI SYNTHETIC SAE 10W-40 is a superior performance, non-friction modified shear stable multigrade gasoline engine oil specifically designed for use in 4-stroke motorcycles and portable power equipment requiring performance lubricants.

PENNZOIL FASTRAC TITANIUM 4T SEMI SYNTHETIC SAE 10W-40 delivers extra protection under high temperature and extreme riding conditions by restraining deposits and long-term damage.

APPLICATION

PENNZOIL FASTRAC TITANIUM 4T SEMI SYNTHETIC SAE 10W-40 suitable use in all Japanese and European motorcycle including high performance and street motorcycle.

BENEFITS

- Provides excellent protection for transmission and wet clutches
- Outstanding high rpm / high temperature protection
- Excellent engine cleanliness; suitable for long drain intervals
- Exceptional engine performance under extreme riding conditions

SPECIFICATIONS

- API SP
- JASO MA2

PENNZOIL FASTRAC TITANIUM 4T SEMI SYNTHETIC SAE 10W-40 (API SP)



TYPICAL PROPERTIES

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 10W-40
JASO Service Category		JASO MA2
Density @30°C, kg/l	ASTM D4052	0.8487
Kinematic Viscosity @40°C, cSt	ASTM D445	98.37
@100°C, cSt	ASTM D445	14.65
Viscosity Index	ASTM D2270	154
Flash Point, °C, Min	ASTM D92	220
Pour Point, °C, Min	ASTM D5950	-36