

PENNZOIL HYDRAULIC HYD68

SUPER SERIES



Review Date: 4th April 2022

PRODUCT DESCRIPTION

PENNZOIL HYD 68 is a super mineral-based hydraulic oils with good oxidation stability and outstanding protection against rust and corrosion in the most demanding of systems while still meeting ISO standards for hydraulic oil. The quality of anti-wear and anti-foam additive package prevents wear of internal components and facilitates the rapid release of entrained air, therefore maximizing hydraulic system efficiency.

APPLICATION

PENNZOIL HYD 68 can be used in a wide range of equipment such as hydraulic systems, plain and anti-friction bearings used in electric motors, gear sets and other equipment where extreme pressure (EP) performance are not required.

BENEFITS

- Good anti-wear protection to extend components life.
- Good antifoam characteristics to ensure smooth operation.
- Resistance to oxidation to prolong oil life.
- Good water separation.

SPECIFICATION

- ISO VG 68

PENNZOIL HYDRAULIC HYD68

SUPER SERIES



Review Date: 4th April 2022

TYPICAL PROPERTIES

TEST	METHOD	TYPICAL RESULT
ISO Viscosity Grade	ISO 3448	68
Density @30°C, kg/l	ASTM D4052	0.8750
Kinematic Viscosity @40° C, cSt	ASTM D7042	68.0
@100° C, cSt	ASTM D7042	9.3
Viscosity Index	ASTM D2270	114
Flash Point, °C, Min	ASTM D92	225
Pour Point, °C, Min	ASTM D97	-12