

PENNZOIL FASTRAC RX 2T

API TC, JASO FB



PRODUCT DESCRIPTION

PENNZOIL FASTRAC RX 2T is specially formulated to handle the demands of high-RPM operation, stop-and-go street riding, and dusty road conditions. It is blended with high-quality lube stocks that naturally provide strong lubricating properties. These base oils are further enhanced with carefully selected additives developed to meet the needs of hard-working motorcycle engines.

APPLICATION

PENNZOIL FASTRAC RX 2T is recommended for use in air-cooled two-stroke engines that require 2T lubricants and operate under high-RPM, stop-and-go, or dusty riding conditions.

BENEFITS

- Good cleaner for exhaust system and system blocking.
- Results in lower smoke emissions from the engine.
- Reduces engine deposits while increasing performance.
- Ensures longer engine life.

SPECIFICATIONS

- API TC
- JASO FB

TYPICAL PROPERTIES

Test	Method	Typical Results
API Service Category		API TC
Density @30°C, kg/l	ASTM D4052	0.8636
Kinematic Viscosity @40°C, cSt @100°C, cSt	ASTM D7042 ASTM D7042	56.6 8.3
Viscosity Index	ASTM D2270	116
Flash Point, °C, Min	ASTM D92	121
Pour Point, °C, Min	ASTM D5950	-6
Colour	ASTM D2896	Red