

PENNZOIL PLATINUM EXTREME SAE 20W-50 MINERAL (API SN/CF)



PRODUCT DESCRIPTION

PENNZOIL PLATINUM EXTREME SAE 20W-50 motor oil is a high-quality mineral motor oil formulated to meet the requirements of gasoline engines that specify an API SN performance level. It is blended using selected base oils and additives to help provide reliable lubrication and protection across a wide range of operating conditions.

The formulation helps reduce oxidation, wear, and deposit formation, contributing to engine cleanliness and stable viscosity performance.

APPLICATION

PENNZOIL PLATINUM EXTREME SAE 20W-50 motor oil is suitable for all vehicles, including both modern and older models equipped with advanced technologies such as turbochargers, direct injection, multi-valve systems, fuel injection, LPG, and NGV. It remains suitable for emission control components, including catalytic converters when used as specified by the OEM.

This oil is backward compatible with earlier API gasoline categories such as API SM, SL, and SJ, making it suitable for use in older vehicles that specify these previous service classifications.

For optimal protection and extended engine life, use PENNZOIL PLATINUM EXTREME and follow the oil-change intervals recommended by your Original Equipment Manufacturer (OEM).

BENEFITS

- Provides superior protection for emission control systems.
- Improves deposit control on pistons and turbochargers at high temperatures.
- Keeps the engine clean for consistent performance.
- Enhances wear protection to help extend engine life.

SPECIFICATIONS

- API SN/CF

PENNZOIL PLATINUM EXTREME SAE 20W-50
MINERAL (API SN/CF)



TYPICAL PROPERTIES

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 20W-50
API Service Category		API SN / CF
Density @30°C, kg/l	ASTM D4052	0.8728
Kinematic Viscosity @40°C, cSt @100°C, cSt	ASTM D7042 ASTM D7042	152.6 17.0
Viscosity Index	ASTM D2270	120
Flash Point, °C, Min	ASTM D92	236
Pour Point, °C, Min	ASTM D5950	-39
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 9,500 @ -15 °C
Total Base Number, mgKOH/g	ASTM D2896	7.3