

PENNZOIL PLATINUM BLITZ SAE 10W-40

SEMI SYNTHETIC (API SQ)



PRODUCT DESCRIPTION

PENNZOIL PLATINUM BLITZ SAE 10W-40 is a premium semi-synthetic motor oil formulated to deliver dependable protection and performance for modern gasoline engines vehicles. Designed to handle everyday driving as well as demanding conditions, it helps maintain engine reliability and efficiency.

The formulation helps maintain engine cleanliness by controlling deposits and sludge while supporting stable lubrication across a wide temperature range. It also assists in protecting modern engine components, including timing chains and emission-control systems, as required for API SQ-level performance.

APPLICATION

PENNZOIL PLATINUM BLITZ SAE 10W-40 is recommended for use in all vehicles equipped with advanced technologies such as turbochargers, direct injection, multi-valve systems, and emission control components including catalytic converters and Gasoline Particulate Filters (GPF).

For reliable protection and extended engine life, use **PENNZOIL PLATINUM BLITZ** and follow the oil change intervals specified by your Original Equipment Manufacturer (OEM).

BENEFITS

- Keeps engine components clean with strong oxidation and deposit control
- Protects against LSPI in modern turbocharged engines
- Reduces timing chain wear for longer durability
- Ensures smooth cold starts with excellent low-temperature performance

SPECIFICATIONS

- API SQ

PENNZOIL PLATINUM BLITZ SAE 10W-40

SEMI SYNTHETIC (API SQ)



TYPICAL PROPERTIES

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 10W-40
API Service Category		API SQ
Density @30°C, kg/l	ASTM D4052	0.8524
Kinematic Viscosity @40°C, cSt @100°C, cSt	ASTM D7042 ASTM D7042	92.5 14.4
Viscosity Index	ASTM D2270	162
Flash Point, °C, Min	ASTM D92	216
Pour Point, °C, Min	ASTM D5950	-36
Low Temperature Viscosity (cP) at Temperature (°C), Max	ASTM D5293	MAX 7000 @ -25
Total Base Number, mgKOH/g	ASTM D2896	7.6