

PENNZOIL FASTRAC RX 4T SAE 40

API SG/CD, JASO MA



Review Date: 16th Mar 2026

PRODUCT DESCRIPTION

Pennzoil Fastrac RX 4T SAE 40 is specially formulated for 4-stroke motorcycles, using a balanced blend of high-quality base oils and carefully selected additives.

It provides reliable lubrication and high-temperature protection required by high-revving motorcycle engines, helping maintain engine cleanliness and smooth operation under a wide range of riding conditions.

APPLICATION

Pennzoil Fastrac RX 4T SAE 40 is recommended for 4-stroke motorcycle engines used in racing, high-performance, street, and off-road applications where a monograde SAE 40 engine oil is specified.

It is also suitable for use in motorcycle transmissions where engine oils meeting API SG or earlier performance levels are specified.

BENEFITS

- Provides protection for the transmission and wet clutches
- Helps maintain engine performance
- Minimizes varnish and sludge formation
- Maintains the cleanliness of the engine and parts
- Help reduce foaming and air entrainment in high speed engines
- Provide excellent protection for air-cooled engines
- Outstanding protection against thermal and viscosity breakdowns

SPECIFICATIONS

- API SG/CD
- JASO MA

PENNZOIL FASTRAC RX 4T SAE 40

API SG/CD, JASO MA



Review Date: 16th Mar 2026

TYPICAL PROPERTIES

TEST	METHOD	TYPICAL RESULT
SAE Viscosity Grade		40
API Service Category		SG/CD
Density @30°C, kg/l	ASTM D4052	0.8808
Kinematic Viscosity		
@40 °C, cSt	ASTM D445	129.5
@100 °C, cSt	ASTM D445	13.4
Viscosity Index	ASTM D2270	98
Flash Point, °C, Min	ASTM D92	210
Pour Point, °C, Min	ASTM D97	- 9