

PENNZOIL FASTRAC TITANIUM 4T

100% SYNTHETIC SAE 10W-40 (API SP)



PRODUCT DESCRIPTION

PENNZOIL FASTRAC TITANIUM 100% SYNTHETIC SAE 10W-40 is a unique fully synthetic lubricant for ultimate engine protection and superior clutch and gearbox operation for high performance 4 stroke motorcycles.

PENNZOIL FASTRAC TITANIUM 100% SYNTHETIC SAE 10W-40 motorcycle oil delivers maximum protection against the harmful effects of all riding conditions. It is the best choice for engines that perform under high temperatures and extreme conditions at high speeds without compromising protection.

APPLICATION

PENNZOIL FASTRAC TITANIUM 100% SYNTHETIC SAE 10W-40 can be used in high performance air and water-cooled 4 stroke motorcycle engines, including race tuned and the ones with gearboxes and wet clutches. It can also be used in motorcycle gearboxes that must be lubricated by engine oils including some gearboxes present in 2 stroke bikes and scooters.

BENEFITS

- Excellent protection for the transmission and wet clutches
- Maximum high RPM/ high temperature protection
- Excellent engine cleanliness – suitable for long drain intervals
- Excellent engine performance and life under extreme driving conditions

SPECIFICATIONS

- API SP
- JASO MA2

PENNZOIL FASTRAC TITANIUM 4T
100% SYNTHETIC SAE 10W-40 (API SP)



TYPICAL PROPERTIES

Test	Method	Typical Results
SAE Viscosity Grade	J300	SAE 10W-40
JASO Service Category		JASO MA2
Density @30°C, kg/l	ASTM D4052	0.8400
Kinematic Viscosity @40°C, cSt	ASTM D445	86.4
@100°C, cSt	ASTM D445	14.3
Viscosity Index	ASTM D2270	171
Flash Point, °C, Min	ASTM D92	228
Pour Point, °C, Min	ASTM D5950	-39