



PRODUCT DESCRIPTION

Pennzoil ATF DEX III is a new generation petroleum based fluid for automatic and power shift transmission. It is formulated to meet the viscosity and frictional requirements of DEXRON® III (H) and MERCON®, Allison C-4 fluid and Caterpillar TO-2 lubricant.

Pennzoil ATF DEX III can be used in passenger cars, trucks and buses, off-highway construction, mining equipment, industrial machinery and power steering system which require DEXRON® III, DEXRON® IIE, DEXRON® II, DEXRON® or MERCON® automatic transmission fluids.

APPLICATION

Pennzoil ATF DEX III is a multi-functional fluid which meets or exceeds the following performance requirements or manufacturers' specifications:

- ✓ DEXRON® III (H)
- ✓ DEXRON®
- ✓ Allison Type C-4
- ✓ Caterpillar TO-2

BENEFITS

- Excellent friction, oxidation and thermal stability
- Outstanding anti-wear performance
- Protects components from harmful attacks by corrosive acids
- Excellent compatibility with seal materials
- Year-round performance
- Multi-functional fluid – reduces inventory
- Assures long equipment life

PENNZOIL ATF DEX III



Review Date: 10th December 2024

TYPICAL PROPERTIES

TEST	METHOD	TYPICAL RESULT
Colour	Vision	RED
Kinematic Viscosity @40 °C, cSt	ASTM D7042	39.1
@100 °C, cSt	ASTM D7042	7.8
Viscosity Index	ASTM D2270	175
Density @30°C, kg/l	ASTM D4052	0.8471
Flash Point, °C, Min	ASTM D92	212
Pour Point, °C, Min	ASTM D5950	- 42